



ALL CONTENTS ©2018 – ALL RIGHTS RESERVED

GUTTERS

AUTHOR: JOHN BOWMAN – EDITOR(S): NACBI EDUCATION
COMMITTEE

NACBI Professional Growth & Support System Self-Assessment
Program Publication

This publication is intended **SOLELY** for use by **PROFESSIONAL PERSONNEL** who are competent to evaluate the significance and limitation of the information provided herein, and who will accept total responsibility for the application of this information. The National Association of Commercial Building Inspectors™ & Thermographers (NACBI) **DISCLAIMS** any and all **RESPONSIBILITY** and **LIABILITY** for the accuracy of and the application of the information contained in these publications to the fullest extent permitted by law.



THIS RESIDENTIAL GRADE GUTTER ON A COMMERCIAL BUILDING HAS BEEN BENT AND DAMAGED.

GUTTERS?

BACKGROUND

There are many different types of gutters but the more common are either the 5 or 6-inch “K” gutter fabricated in .032 aluminum. This is usually installed for a residential use and is therefore capable of handling watershed levels found in this setting. The downspouts normally installed here are 3-inch x 4-inch in size.

Almost all large commercial buildings should have a “commercial” grade gutter system. This is usually at least a 5-inch box gutter (or larger) fabricated in at least 24-gauge steel. The downspouts are usually either 3-inch x 4-inch or 4-inch x 5-inch depending on the amount of water they need to handle. The use of non-commercial grade gutters on commercial buildings will only result in unnecessary repair costs later.

Some Common discrepancies:

- 🔧 Clogged, Overflowing Systems:
- 🔧 Damaged or bent runs that restrict water-flow;
- 🔧 Loose Gutters;
- 🔧 Improper slope or Sagging Gutters:
- 🔧 Cracks where fasteners pass through:
- 🔧 Undersized Gutters
- 🔧 Corroded, Leaky Gutters;
- 🔧 Joint separation.



IMPROPER SLOPED GUTTER.



INSPECTION PROCEDURE/REPORTING

Recommendations/Insight: Commercial grade gutters can withstand the abuse that comes along with a commercial building setting, be it maintenance contractors and ladders or higher watershed levels, due to the materials used and overall design. As a result, replacement or repair of non-commercial gutters may occur more often.

Probability of Costs: (2018 Costs)

Labor & Material:

- 5" "K"- .032" thick aluminum - \$12.00/lf + costs of downspouts, attachments, etc.
- 5" steel galvanized, 28-gauge metal - \$9.75/lf + costs of downspouts, attachments, etc.